











Hebeschlingen					
Anschlagart	direkt	geschnürt	umlegt	umlegt	umlegt
Neigungswinkel	-	-	-	bis 45°	bis 60°
Kennfarbe	Tragfähigkeit in kg				
violett	1000	800	2000	1400	1000
weiß	1500	1200	3000	2100	1500
grün	2000	1600	4000	2800	2000
gelb	3000	2400	6000	4200	3000
grau	4000	3200	8000	5600	4000
rot	5000	4000	10000	7000	5000
braun	6000	4800	12000	8400	6000
blau	8000	6400	16000	11200	8000
orange	10000	8000	20000	14000	10000
orange	12000	9600	24000	16800	12000
orange	15000	12000	30000	21000	15000
orange	20000	16000	40000	28000	20000
orange	25000	20000	50000	35000	25000
orange	30000	24000	60000	42000	30000

Hehebänder					
Anschlagart	direkt	geschnürt	umlegt	umlegt	umlegt
Neigungswinkel	-	-	-	bis 45°	bis 60°
Kennfarbe	Tragfähigkeit in kg				
violett	1000	800	2000	1400	1000
grün	2000	1600	4000	2800	2000
weiß	2500	2000	5000	3500	2500
gelb	3000	2400	6000	4200	3000
grau	4000	3200	8000	5600	4000
rot	5000	4000	10000	7000	5000
braun	6000	4800	12000	8400	6000
blau	8000	6400	16000	11200	8000