



Schäkkel hochfest vergütet, geschweißt mit Schraubbolzen

WLL kg	b1 mm	b3 mm	d1 mm	d3 mm	d4 mm	h1/h2 mm	Gewicht kg
500	12	19	6	17	8	28	0,05
750	13	21	8	21	10	31	0,08
1.000	16	26	10	26	12	36	0,14
1.500	18	29	11	28	14	42	0,22
2.000	21	33	13	30	16	48	0,33
3.250	27	43	16	42	20	60	0,65
4.750	32	51	19	48	22	71	0,97
6.500	36	58	22	57	27	84	1,46
8.500	43	68	25	62	30	95	2,39
9.500	46	74	29	69	33	103	3,15
12.000	52	82	32	78	36	119	4,32
13.500	57	92	35	86	39	133	5,67
17.000	60	98	38	94	42	146	7,79
25.000	73	127	44	112	52	178	12,51
35.000	83	146	51	135	60	197	18,5
55.000	106	184	63	158	72	267	37,58

Schäkkel hochfest vergütet, geschweißt mit Schraubbolzen, Mutter und Splint

WLL kg	b1 mm	b3 mm	d1 mm	d3 mm	d4 mm	h1/h2 mm	Gewicht kg
500	12	19	6	17	8	28	0,07
750	13	21	8	21	10	31	0,1
1.000	16	26	10	26	12	36	0,18
1.500	18	29	11	28	14	42	0,25
2.000	21	33	13	30	16	48	0,37
3.250	27	43	16	42	20	60	0,71
4.750	32	51	19	48	22	71	1,27
6.500	36	58	22	57	27	84	1,78
8.500	43	68	25	62	30	95	2,52
9.500	46	74	29	69	33	109	3,53
12.000	52	82	32	78	36	119	5,04
13.500	57	92	35	86	39	133	6,84
17.000	60	98	38	94	42	146	8,78
25.000	73	127	44	112	52	178	14,09
35.000	83	146	51	135	60	197	20,84
55.000	106	180	65	145	72	267	42,3
85.000	127	190	76	165	83	330	65,25
120.000	148	229	92	203	96	390	115