









	1-Strang		2-Strang				3-/4-Strang		Kranzkette		
											
<b>Neigungswinkel <math>\beta</math></b>	-	-	bis 45°	45° -60°	bis 45°	45° -60°	bis 45°	45° -60°	-	-	<b>Neigungswinkel <math>\beta</math></b>
<b>Belastungsfaktor</b>	1	0.8	1.4	1	1.12	0.8	2.1	1.5	2x2	1.6	<b>Belastungsfaktor</b>
<b>Ketten-Nenndicke (mm)</b>	<b>Tragfähigkeit in kg</b>										<b>Ketten-Nenndicke (mm)</b>
4	500	400	700	500	560	400	1050	750	2000	800	4
5	750	600	1050	700	840	600	1570	1120	3000	1200	5
6	1000	800	1400	1000	1120	800	2100	1500	4000	1600	6
7	1500	1200	2100	1500	1700	1200	3150	2250	6000	2400	7
8	2000	1600	2800	2000	2240	1600	4250	3000	8000	3200	8
10	3200	2500	4500	3200	3550	2500	6700	4750	12500	5000	10
13	5000	4000	7100	5000	5600	4000	10000	7500	20000	8000	13
16	8000	6300	11200	8000	9000	6300	17000	11800	32000	12500	16
19	11000	8800	15400	11000	12300	8800	23100	16500	44000	17600	19
22	15000	12000	21200	15000	17000	12000	32000	22400	60000	24000	22
26	20000	16000	28000	20000	22400	16000	40000	30000	80000	32000	26
32	32000	25000	45000	32000	35500	25000	63000	47500	125000	50000	32




Güteklasse 8, DIN 5688

Allgemeines

Blatt

6

Anschlagketten VIP Sondergüte

Ketten-Nenn- durchmesser (mm)	Einzelstrang	Doppelstrang mit Neigungswinkeln		Drei- und Vierstrang mit Neigungswinkeln	
		0°- 45°	45°- 60°	0°- 45°	45°- 60°
					
<b>Tragfähigkeit in kg</b>					
4	630	880	630	1320	950
6	1500	2100	1500	3150	2250
8	2500	3500	2500	5250	3750
10	4000	5600	4000	8400	6000
13	6500	9100	6500	13650	9750
16	10000	14000	10000	21000	15000
20	16000	22400	16000	33600	24000
22	20000	28000	20000	42000	30000